


Radio Module Medium Range (MR)

Includes:

- Medium range radio module



More info about the product!



Radio Module Medium Range (MR) SKU is: AS-XBEE-MR-2.4-INT-01

Get a discounted bulk price on this product for orders of 50 units or more. Contact us at info@ardusimple.com to get a quote.

Description

The Medium Range version of our Radio Module, including an embedded antenna.

This is the recommended radio for your line of sight projects. You will be able to send RTK corrections up to 1200m with line of sight, in point-to-point configuration (not suitable for multirover).

This radio is only sold in pairs, pre-configured for unidirectional communication (Base to Rover). The radios are labelled with "B" for the base and "R" for the rover.

Good to know:

- Compatible with all ArduSimple boards or any other boards with XBee socket in the market.
- This radio is included in our [simpleRTK2B - Starter Kit MR](#).

Specifications


Interfaces

- UART
- RS232 ([requires accessory](#))

MR radio features

- Communication: Unidirectional Point-to-Point (maximum 1 rover)
- Frequency: ISM 2.4 GHz
- Output power: 6.3 mW (8 dBm)
- Range in line of sight:
 - Urban: 250 meters
 - Rural: 600 meters
 - Rural with complete RF line of sight: 1'200 meters
- Antenna type: internal
- Operating temperature Range: -40 to +85deg
- Documentation: RED, RoHS, FCC, IC

Image Gallery



Documentation

User Guide <https://www.ardusimple.com/xbee-antenna-installation-guide/>

Radio Module Medium Range (MR) includes free basic technical support. Contact info@ardusimple.com for more information.

Data and descriptions in this document are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product appearance.